

# **Preferred Pack<sup>®</sup>**

## **"ALL-IN-ONE"**

### **COMPACT L'SEALER AND SHRINK CHAMBER ALL BUILT INTO ONE MACHINE**



### **Model PP76ST**

This unique "All-IN-ONE" L'Sealer and Shrink Chamber is only 56" in Total Length and Features a 16" W x 22" L Seal Area. Featuring New "Band Seal Technology" - Will Seal and Shrink PVC or Polyolefin Shrink Films with no Smoke or Residue.



New "Band Seal Technology" Will Seal and Shrink PVC or Polyolefin Shrink Films with No Smoke or Residue



\* Optional Feature: Powered Discharge Conveyor Available



\* Optional Feature: Magnet Hold Down During Seal Cycle. Available on PP76ST only.

Heavy Duty Plexiglass Hood - Fully enclosed sealing and shrinking operation for maximum operator safety

Magnetic Arm Hold Down During Shrink Cycle

Dual Mode Switch  
1-Seal only  
2-Seal and Shrink

Seal Timer

Shrink Timer

Temperature Control

Adjustable Table Lowers 3 1/2" for high products

Pin Wheel Hole Punch

Easy Load Film Holder

Heavy Duty Locking Casters

The operator places the product on the package loading tray in between the two layers of centerfold film. The operator then moves the package into the sealing area and lowers the hood. Once the hood is lowered, the operator applies pressure to make the seal. Once the seal is made, the operator releases the hood and the Automatic Magnetic Hold Down keeps the hood down until the film has shrunk. When the shrink time is completed, the hood will automatically return to the up position and the operator may remove the completed package. Complete cycle time is approximately 5-6 seconds.

MODEL	POWER			WT.	SEAL DIMEN.		MACHINE DIMEN.			MAX. FILM WIDTH	MAX. PKG. HEIGHT
	VOLTS	PHASE	AMPS		W	L	L	W	H		
PP43ST	110	1	20	275	12	17	49	26	45	20"	8"
PP76ST	220	1	25	350	16	22	56	30	45	24"	10"

\*Backed by Preferred Packagings exclusive 1 year warranty

AUTHORIZED DISTRIBUTOR