

SAVEMA 20 i&c&tr SERIES THERMAL TRANSFER OVERPRINTERS

53 C AB
107 C AB



Common Specifications for All Printers


Software: SAYASIS Template Design (Date and Time, Custom Formatted Date and Time, Text, Text Block, Merge Fields, Database Support, Counter, Logo, 1D / 2D Barcodes, GS-1 Barcodes, Table Creation Support and User-Friendly Interface) Windows Driver Support, Teklynx Software (Code-soft, Labelview and Label Matrix Support), Emulator Support, Printer Management with SPPL (Savema Protocol) Commands, Printer Control with Remote Control)

Barcodes: 1D Barcodes (EAN-13, EAN-8, CODE 128, CODE 39, CODABAR, ITF 2of5, ITF 14, UPC-A,UPC-E ...), 2D Barcodes (Datamatrix, QR Code, PDF417, Aztec code...), GS-1 Barcodes (GS1-128, GS1-Datamatrix, GS1-Databar Barcodes)

Resolution: 300dpi (12 dots/mm) horizontally and vertically

Operating Temperature: 1 °C - 55 °C (34°F-131°F)

Memory: 5000 Template Storage Capacity, 1GB Internal Memory, Up to 16GB SD Memory Card Support, Up to 32GB USB Memory Support



Specifications	53 C AB (Continuous for Autobag)	107 C AB (Continuous for Autobag)
Print Area	53 mm x 125 mm (Standard) 53 mm x 500 mm (Optional)	107 mm x 125 mm (Standard) 107 mm x 250 mm (Optional)
Print Speed	10 - 800 mm/sec	10 - 600 mm/sec
Production	500 prints/min	300 prints/min
Ribbon Widths & Length	35mm, 55 mm (1,4" - 2,2") & 600 meters (656yards) loaded ribbon	110 mm (4,28") & 600 meters (656yards) loaded ribbon
Power Supply	100-240V 50-60 Hz	
Air Supply (Bar)	Min. 2 bar - Max. 5 bar	
Input/Outputs	Print Signal/Fault Signal, Busy Signal	
Output Messages	Missing Print Error, Encoder Error, Update Error, Contact Error, Ribbon Break / Not Found Error, Remaining Ribbon Quantity, Number of Printed Templates, Number of Prints per Minute	
Connection Types	Relay(NPN, PNP) - Photocell(NPN, PNP)	
Communications	RS-232, Ethernet, USB	
Ribbon Save Modes	Vertical Ribbon Save Mode	
Advanced Control	7" Touch Screen Control, Template Changing while Running, Contrast, Print Delay, Template-Specific Adjustment, Internal Contact Signal, Multi-print Contact Signal, Template Shifting, Template Rotation	
Operator Interface	7" 800x480 Pixels Resolution, Full-color display, Password protection on menus, Multi-language(18) support	
Weight (Printer)	6 Kg.	6,5 Kg.
Dimensions	178mm H x 220mm W x 210,5mm D	178mm H x 220mm W x 265,5mm D

